

5 3 1	5 3 8	耐火パイプ	株式会社 エーアンドエー マテリアル
06.2	06.2		

品 種	呼び径	価 格
定尺管 (内管VU)	40 × 2000	2,300
	50 × 2000	2,870
	65 × 2000	4,110
	75 × 2000	4,880
	100 × 2000	7,090
TP-VU	125 × 2000	10,140
	150 × 2000	12,770
	65 × 2650	6,310
長尺管 (内管VU)	75 × 2350	6,410
	75 × 2650	7,370
	75 × 3000	8,420
TP-VU	100 × 2350	9,360
	100 × 2650	10,680
	100 × 3000	12,210
	125 × 2650	15,080
	150 × 2650	18,770

品 種	呼び径	価 格
定尺管 (内管VP)	40 × 2000	3,170
	50 × 2000	3,970
	65 × 2000	5,570
	75 × 2000	6,670
	100 × 2000	9,680
TP-VP	125 × 2000	13,740
	150 × 2000	17,330
	65 × 2650	8,540
長尺管 (内管VP)	75 × 2350	8,610
	75 × 2650	9,920
	75 × 3000	11,360
TP-VP	100 × 2350	12,470
	100 × 2650	14,430
	100 × 3000	16,690
	125 × 2650	20,200
	150 × 2650	25,330

5 4 1	受口付 耐火パイプ
05.1	

TP-R	呼び径	価 格
	75×2710	14,450
	100×2710	19,800

(単位：円/本)

5 4 3	耐火パイプワンタッチ継手	株式会社 エーアンドエー マテリアル
改定2006.2		

品 種	呼び径	価 格
DS	40	1,060
	50	1,220
	65	1,500
	75	1,640
	100	2,210
	125	3,360
IN	150	4,750
	50 × 40	1,170
	65 × 40	1,310
	65 × 50	1,330
	75 × 40	1,400
	75 × 50	1,490
	75 × 65	1,620
	100 × 40	1,670
	100 × 50	1,710
	100 × 65	1,950
DL	100 × 75	2,040
	125 × 65	2,400
	125 × 75	2,500
	125 × 100	3,080
	150 × 75	3,210
	150 × 100	3,640
	150 × 125	4,260
	40	1,440
	50	1,690
	65	2,150
DLI	75	2,490
	100	3,630
	125	5,520
	150	8,230
	50 × 40	2,860
45° L	65 × 50	3,270
	75 × 50	3,330
	100 × 50	4,030
	100 × 75	4,510
45° Y	40	1,360
	50	1,580
	65	1,990
	75	2,210
	100	3,120
	125	4,490
	150	6,180
	40	1,890
45° Y	50	2,300
	65	3,010
	75	3,540
	100	5,480
	125	8,500
150	13,790	

品 種	呼び径	価 格
45° Y	50 × 40	2,170
	65 × 40	2,620
	65 × 50	2,720
	75 × 40	2,920
	75 × 50	3,060
	75 × 65	3,400
	100 × 40	3,850
	100 × 50	4,050
	100 × 65	4,470
	100 × 75	4,740
	125 × 100	7,390
	150 × 100	10,910
LL	40	2,300
	50	2,520
	65	3,070
	75	3,640
	100	5,080
	125	7,360
	150	10,410
	100 × 75	7,370
	40	2,130
	50	2,500
LT	65	3,300
	75	3,830
	100	5,890
	125	9,260
	150	14,600
	50 × 40	2,380
	65 × 40	2,810
	65 × 50	2,930
	75 × 40	3,170
	75 × 50	3,310
WLT	75 × 65	3,670
	100 × 40	4,180
	100 × 50	4,400
	100 × 65	4,870
	100 × 75	5,160
	125 × 65	6,750
	125 × 75	7,510
	125 × 100	8,160
	150 × 65	9,920
	150 × 75	10,330
WLT	150 × 100	11,780
	150 × 125	13,600
	65	5,060
	75	6,240
	100	10,580
100 × 75	7,230	
125 × 100	13,950	

品 種	呼び径	価 格
INH	65 × 50	3,100
	75 × 50	3,490
	100 × 75	4,330
	40	1,890
	50	2,230
	65	2,920
	75	3,490
	100	5,240
	125	8,070
	150	12,430
DT	50 × 40	2,120
	65 × 40	2,590
	65 × 50	2,700
	75 × 40	2,810
	75 × 50	2,950
	75 × 65	3,300
	100 × 40	3,770
	100 × 50	3,920
	100 × 65	4,300
	100 × 75	4,580
ES	125 × 75	6,670
	125 × 100	7,060
	150 × 75	9,800
	150 × 100	10,920
	40	1,820
	50	2,150
	65	2,550
	75	2,790
	100	3,860
	125	5,540
ESS	150	7,760
	75	4,700
	100	5,680
	40	2,720
	50	2,990
DSH	65	3,840
	75	4,360
	100	5,320
	125	7,140
	150	10,320
VS	40	1,410
	50	1,650
	65	2,010
	75	2,310
	100	3,390
YB	125	4,940
	150	7,080
	40	2,750
	50	3,120
	65	3,690
75	4,350	
100	5,900	

5 3 2	耐火パイプ継手
改定2006.2	

品 種	呼び径	価 格
CO	40	980
	50	1,280
	65	1,430
	75	1,650
	100	2,470
	125	3,730
	150	5,650
HB	90	3,400
	90A	3,480
	90B	9,810
	90L	12,020
	10	5,220
	S	4,650
Y-B	40	2,500
	50	2,840
	65	3,350
	75	3,950
	100	5,360
	125	7,640
150	10,720	

5 3 6	ボンド
改定2006.2	

品 種	価 格
ASボンド 1kg	1,050
AS目地 2kg	1,050

耐火パイプ・
鑄鉄管・集合管